



SM07S4

Wide View System System includes (1) C305 Camera

Engineered to meet the commercial demands needing a wide view, without the fisheye. This 7" LCD Monitor has a clear, crisp view in our durable housing. The monitor supports up to (3) Verity cameras. The SM07S4 includes our ADD21U "S" mount and (1) 65' camera cable. Ideal for limited installation space!

MONITOR SPECIFICATIONS (Part #MK07S)

- (Monitor part #MK07S)
- Screen size: 7-inch digital screen (16:9)
- High Resolution: 1024 x 600 Pixel (RGB)
- System: PAL/NTSC Auto Select
- Contrast: 400:1
- Brightness: 300 cd/m2
- Power supply: DC 12V~24V with reverse polarity protection
- Operation temperature: -30°~80°C
- Storage temperature: -20°~70°C
- Monitor view angle: Horz. L (70) R (70) Vert. UP (50) DOWN (70)
- 3 AV with shrink tube labeled trigger wires,
- Auto blue screen if no signal on the activated channel.
- Size: 141 x 103 x 25 mm.
- Weight: 418 g.



Features: Removable HD sunshade, LCD screen, LED blue light buttons, high-quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons: reversing image delay time 0~10s, Mirror/Normal image, plus horizontal flip, multi-language.

CAMERA SPECIFICATIONS (Part #C305)

CAMERA SPECIFICATIONS

- Camera Part #C305)
- Horizontal Resolution: 800 TV Lines
- TV System: NTSC
- Image Type: CMOS PC1058
- Aluminum Housing
- Waterproof: IP69K
- Power Supply: DC 12V (powered from the monitor)
- Operating Temperature:-20°C~ +75°C
- Viewing Angle: 180-degrees horizontal.



574-807-6002 www.veritysafe.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

Woman-Owned

A division of Component Solution Services, LLC.

Est. 2002

Subject to change without notice